

2.8kw 4kw Diesel Chemical Pumps Self Priming Diesel Water Pump

Basic Information

. Place of Origin: China . Brand Name: **GET** ISO CE Certification: · Price: Negotiable • Delivery Time: 15-20 workdays

LC, T/T, PayPal, Western Union, Small-Payment Terms:

amount payment, Money Gram



Product Specification

. Type: Diesel Chemical Pumps Suction/discharger Port

Diameter Mm(inch):

50(2'). 80(3'). 100(4'). 150(6')

• Discharge Capacity m³/h): 30 40 110 150 • Total Head Lift: 25m 26m 22m 20m 80 120 180 180 Self-priming Time (s/4m): Max Suction Head: 8m 8m 8m 6m

• Rotation Speed (r/min): 3600 • Noise Level Db(A)/7m): 85

• Overall Dimension(mm): 510x455x640. 560x455x655. 650x470x700.

770x574x785

• Dry Weight: 44kg 50kg 71kg 95kg

• Engine Model: GET50

· Rated Power: 2.8kw 4kw 6.3kw 8.5kw

• Fuel Consumption G/kw.h: 288 285 281 281 Disclessor (2003). 047 000 440 400

Product Description

GET Diesel Chemical Transfer Pumps Self-Priming Capability

Diesel chemical transfer pumps have specific features that make them well-suited for efficiently and safely transferring chemicals. Here are some notable features of diesel chemical transfer pumps:

| Suction/discharger Port Diameter Mm(inch): | 50(2'). 80(3'). 100(4'). 150(6') |
|-----------------------------------------------|-------------------------------------------------------|
| Total Head Lift: | 25m 26m 22m 20m |
| Max Suction Head: | 8m 8m 8m 6m |
| Noise Level Db(A)/7m): | 85 |
| Dry Weight: | 44kg 50kg 71kg 95kg |
| Rated Power: | 2.8kw 4kw 6.3kw 8.5kw |
| Displacement (cm³): | 247 296 418 498 |
| Fuel Tank Capacity: | 13.5L |
| Type: | Diesel Chemical Pumps |
| Discharge Capacity(m³/h): | 30 40 110 150 |
| Self-priming Time (s/4m): | 80 120 180 180 |
| Rotation Speed (r/min): | 3600 |
| Overall Dimension(mm): | 510x455x640. 560x455x655. 650x470x700. 770x574x785 |
| Engine Model: | GET50 |
| Fuel Consumption G/kw.h: | 288 285 281 281 |
| Starter System: | Recoil Starter |
| | |

Portable and Skid-Mounted: Diesel chemical transfer pumps are designed to be portable and can be mounted on skids or trailers for easy transportation and mobility. This portability allows for flexibility in various applications, where the pump can be easily relocated and used where needed.

Flow Control and Pressure Regulation: Diesel chemical transfer pumps may incorporate flow control mechanisms, such as adjustable impeller diameters or variable speed drives, to regulate the flow rate of chemicals. Pressure regulation devices, such as pressure relief valves, are also commonly incorporated to protect the pump and the system from excessive pressure. Safety Features: Diesel chemical transfer pumps often include safety features to prevent damage or accidents. These may include overheat protection, low oil pressure shutdown, spark arrestors, and emergency stop buttons. Safety measures are crucial when handling potentially hazardous chemicals to ensure the safety of personnel and equipment.

Maintenance and Serviceability: Diesel chemical transfer pumps are designed for easy maintenance and serviceability. They often have accessible components, such as quick-open covers or removable parts, for convenient inspection, cleaning, and repair. Easy maintenance reduces downtime and ensures the pump operates at its optimal performance.

Diesel chemical transfer pumps are essential equipment for efficiently and safely transferring chemicals in various industrial applications. Their robust construction, chemical compatibility, self-priming capabilities, and mobility make them reliable and versatile for handling a wide range of chemical transfer needs.



| SKRT1ps | | Dissert water pump | Disself water pump | Dised with pump | Destroyer |
|--------------------------------------|---------|--------------------|--------------------|-----------------|------------|
| BSGEE Sustan Discharger Fot Diameter | see jeg | 8901 | 1001 | 1000 | 19985 |
| B. A. B. B. Charles ye reportly | m/h | 20 | . 60 | 110 | *** |
| EZBETON NO.CE | | 27 | | п | 28 |
| BRHS Set-pring Time | 100 | ** | 100 | 190 | - |
| EAST lies seeling basel | - | 4 | | | |
| NE folder-speed | rings. | 3600 | 3600 | 3600 | 300 |
| RAST NOOLSON | docum | ** | * | | |
| HRIT + Grand Ginarrion | - | 517107540 | 500 100 500 | 8801/09790 | 779/07/785 |
| P III Dry swight | ing | 44 | 40 | 71 | - 10 |
| MEDICAL Expression | | BETTER | DETITAL | CETTONPA | genue |
| MERCH RANGE PROFES | w | 13. | 4 | 63 | 85 |
| EASE Fui resumption | plean | 266 | 266 | 261 | 201 |
| UB Deplement | con! | 341 | 296 | 418 | 466 |
| B B chult Stume symm | | Ploof Bator | Please starter | Note that | Receivable |
| 東部港 Factoric operty | - h | 98 | 0.5 | 48.5 | 155 |
| HERT FIR Contrasus entreprend | Te . | 10 | 10 | | |



GET Wuxi Guangertai Power Machinery Co.,Ltd



13813650506



2415819289@qq.com



@ dieselenginepumps.com