Wuxi Guangertai Power Machinery Co.,Ltd dieselenginepumps.com

Green 6kw Silent Generator 6500T Silent Genset 220V Single Phase

Basic Information

Place of Origin: China
Brand Name: GET
Certification: ISO CE
Price: Negotiable
Delivery Time: 15-20 workdays

 Payment Terms: LC, T/T, PayPal, Western Union, Smallamount payment, Money Gram



Product Specification

• Rated Frequency: 50hz 60hz

Rated Output(kw): 2.5 2.8/ 4.5 4.8/ 4.8 5.0/ 5.7 6.0/ 6.0 6.3
Max Output (kw): 2.7 3.0/ 5.0 5.2/ 5.2/5.5/ 6.3 6.9/ 6.8 7.7

• Rated Voltage (V): 220V Or As Request

• Rated Currency (A): 11.3 12.7/ 20.4 21.8/ 21.8 22.7/ 25.9 27.2/

27.2 28.6

Rated Rotation Speed

(r/min):

3000 3600

Phase No.: Single Phase

Power Factor: 1Insulation Grade: FPole Number: 2

Excitation Mode: Self-excitation & Constant Voltage (AVR)

Panel Type: General PanelReceptacle: Two Receptacles

Commention Date: Milliand

Product Description

GET6500T Silent Diesel Generator Green Quiet Diesel Generator

A quiet diesel generator is a type of generator that is designed to produce less noise compared to conventional diesel generators. They are specifically engineered with noise-reducing features and technologies to minimize the sound output during operation. Here are some key aspects and features that contribute to the quiet operation of a diesel generator: Soundproof Enclosure: Quiet diesel generators often come equipped with a soundproof enclosure or housing. The enclosure is constructed using materials that absorb and dampen the noise generated by the engine and other components. This helps to reduce the overall noise level emitted by the generator.

Acoustic Insulation: The soundproof enclosure is lined with acoustic insulation material, such as foam or specialized noise-reducing materials. These materials help to absorb and block sound waves, further reducing the noise produced by the generator.

Vibration Isolation: Noise reduction in diesel generators also involves isolating vibrations from the engine and other moving parts. Special rubber mounts or anti-vibration pads are used to dampen vibrations, preventing them from being transmitted as noise

Control System: The control system of a quiet diesel generator may have features that allow for noise reduction. For example, the generator may automatically adjust the engine speed or load based on the power demand, optimizing fuel consumption and minimizing noise levels.

Noise Level Specifications: Quiet diesel generators are typically labeled with their noise level ratings. The noise level is measured in decibels (dB) and is usually specified at a certain distance from the generator, such as 7 meters (23 feet). Lower dB ratings indicate quieter operation.

dB ratings indicate quieter opera	tion.				
Rated Frequency:	50hz 60hz				
Max Output (kw):	2.7 3.0/ 5.0 5.2/ 5.2/5.5/ 6.3 6.9/ 6.8 7.7				
Rated Currency (A):	11.3 12.7/ 20.4 21.8/ 21.8 22.7/ 25.9 27.2/ 27.2 28.6				
Phase No.:	Single Phase				
Insulation Grade:	F				
Excitation Mode:	Self-excitation & Constant Voltage (AVR)				
Receptacle:	Two Receptacles				
DC 12V Output:	Connection Pole Output				
Dry Weight (kg):	164 150 150 153 161				
Noise Level (7m):	72 DB				
Engine Type:	Single Cylinder, Vertical, Four Stroke, Direct Injection, Air-cooled				
Displacement(ml):	296 418 456 498 531				
Compression Ratio:	20:01, 19:01				
Starting System:	Electric Start				
Lube Oil Brand:	CD Grade Or SAE10W-30, 15W-40				
Starting Motor Capacity:	12V 0.9KW/ 12V 1.2KW				
Battery Capacity:	12V 30Ah				
Fuel Tank Capacity (L):	15				
Rated Output(kw):	2.5 2.8/ 4.5 4.8/ 4.8 5.0/ 5.7 6.0/ 6.0 6.3				
Rated Voltage (V):	220V Or As Request				
Rated Rotation Speed (r/min):	3000 3600				
Power Factor:	1				
Pole Number:	2				
Panel Type:	General Panel				
Connection Pole:	Without				
Overall Dmension(mm):	945*555*700				
Working Assorting Weight (kg):	179 185 186 186 187				
Structure Type:	Silent Type				
Cylinder Nobore X Stroke (mm):	1-78x62/ 1-86x72/ 1-88x75/ 1-92x75/ 1-95x75				
Rated Power:	3.68/3000-4/3600. 5.7/3000-6.3/3600. 6.5/3000-7.2/3600. 7.6/3000-8.2/3600. 8.1/3000-8.7/3600				
Lubrication System:	Pressure Splashed				
Fuel Type:	0#(summer)-10#(winter)-35#(chillness) Diesel				
Lube Capacity (L):	1.1/ 1.65				
Charging Generator Capacity:	12V 8.3A				
Fuel Consumption (g/kw*h):	≤280				

Quiet diesel generators are commonly used in settings where noise reduction is crucial, such as residential areas, outdoor events, and locations with noise restrictions. They offer the advantage of providing reliable power while keeping noise disturbances to a minimum. However, it's important to note that even quiet diesel generators will still produce some level of noise during operation, albeit significantly reduced compared to standard generators.



			CETTOME			
BERE Osterbanery Dr.)	0013000	100.700001	- N	0019000	100,1900001	
BERN Concepted (AV)	28.28	65.43	48.53	17.40	60 63	
BARR No. name (NV)	37.30	10.10	17.10	63.69	68.32	
BEE D.N. Platest vollage (5)	SECURITIES PROFESSION OF A PROPERTY.					
BERE Paletonerry (4)	712 127 204 218 214 227 203 272 272 208					
EXPRIS Finish Address speed Colone 1	112 127	200 213	3000 3000	207.212	22.00	
BIR Chair M.	## trouting					
SHEET Francis Solley (Cos. ©)	THE PROPERTY OF THE PARTY OF TH					
BORRES TOWNS TOWNS						
BIR THE CARDON	1					
Big of Cycleton male	A SMEX / Black / Sub-participal representation (
ENERG Provi Spo	PRES (even from					
BORD TOWN TOW	A 1 6 6 6 6 7 to contain					
Bit 686 Constitution pris	A Billion					
BROK MY OF MY ARM	MARINE Committee only a sized					
BIRTH Grand Streeting LL (Walt) (mg)	647-027-04	8650000	985 555 790	647 TOT TO	86.9879	
BE Do wint I to I	MA - 100 - 100	100	150	107	B0 500-10	
EVENT TO SERVE STATES AND ADDRESS OF THE PARTY OF T	179	- 10	160	100		
CONTROL DOG NAME OF THE PARTY O	79	- 2	- 10	- 10	- 2	
BEREZ Trades has	- 4		Sheet how			
SIDERS Corporated	DETURE OFFINE OFFINE OFFINE					
SIDER Course Type	BETTER DETTERA DETTERA DETTERA DETTERA DELL'ADARDO DEL					
SOME AND	1-1752 1-0772 1-0775 1-0775 1-0775					
BIRE Displacement or	1-19-60	68	450	400	500	
Bit this property (see)	3390	5.00000.6.00000	6.5/2000 7.2/2000	14/2000 5 1/2000	81700004 7786	
END Communication	7007	1961	1000 L	1974	1961	
ERFOLLATION SAND	En Villet Property shaped					
AND THE CONTRACT SPACES	E.D. VARENT, Pressure sylvathed					
MIRRIE FLAT NO.	04 (夏末) -104 (高末) -164 (衛春) 報義 desal(4 summer) -164 (sinter) -164 triiness desal					
MEAN CLASS III STORY	CD great or GM GM, ML, 1997-60					
PERSONAL Later companies (L.)	1.5	1.65	145	1.46	1.66	
BUSINESS Starting motor squartly (19-44)	100 biles	12V COM	501 6.0041	120 1,200	107 1,000	
ESESSES Charges personal reports V-A	50V 8.36	129 8.56	SIV AM	50Y 8.36	129 8.56	
BRANK Schreigenbrig-At-1	129 3044 137 3644					
MERRE Parconantin (staft)	+289	+290	<380	<290	<380	
MERRE TWEEN INCOME ILI	- 11	19	13	70	19	
BYESFERR CORNING OWING SING N	- 11					

GET Wuxi Guangertai Power Machinery Co.,Ltd

13813650506

2415819289@qq.com

@ dieselenginepumps.com

NO.88 Shenxing East Road, Wanshi Town, Yixing City,CHINA