

7500T Silent Diesel Generator 72 DB Quiet Portable Diesel Generator

Basic Information

. Place of Origin: China Brand Name: **GET** ISO CE · Certification: · Price: Negotiable • Delivery Time: 15-20 workdays

LC, T/T, PayPal, Western Union, Small-Payment Terms:

amount payment, Money Gram



Product Specification

. Rated Frequency: 50hz 60hz

Rated Output(kw): 2.5 2.8/ 4.5 4.8/ 4.8 5.0/ 5.7 6.0/ 6.0 6.3 • Max Output (kw): 2.7 3.0/ 5.0 5.2/ 5.2/5.5/ 6.3 6.9/ 6.8 7.7

220V Or As Request • Rated Voltage (V):

• Rated Currency (A): 11.3 12.7/ 20.4 21.8/ 21.8 22.7/ 25.9 27.2/

27.2 28.6

Rated Rotation Speed

(r/min):

3000 3600

• Phase No.: Single Phase

Power Factor: F Insulation Grade: • Pole Number: 2

Excitation Mode: Self-excitation & Constant Voltage (AVR)

Panel Type: General Panel . Receptacle: Two Receptacles

Cammantian Dala

Product Description

GET7500T Silent Diesel Generator Red Portable Silent Generator

A quiet diesel generator is a type of generator that is designed to produce less noise compared to conventional diesel generators. They are specifically engineered with noise-reducing features and technologies to minimize the sound output during operation. Here are some key aspects and features that contribute to the quiet operation of a diesel generator: Soundproof Enclosure: Quiet diesel generators often come equipped with a soundproof enclosure or housing. The enclosure is constructed using materials that absorb and dampen the noise generated by the engine and other components. This helps to reduce the overall noise level emitted by the generator.

Muffler and Exhaust System: A quiet diesel generator is typically fitted with a high-quality muffler and an efficient exhaust system. The muffler dampens the noise created during the combustion process, while the exhaust system is designed to minimize vibration and noise transmission.

Vibration Isolation: Noise reduction in diesel generators also involves isolating vibrations from the engine and other moving parts. Special rubber mounts or anti-vibration pads are used to dampen vibrations, preventing them from being transmitted as noise

Engine Design: Quiet diesel generators may incorporate advanced engine designs and technologies that reduce noise emissions. This can include optimized combustion processes, improved engine insulation, and reduced mechanical friction. Cooling System: The cooling system of a quiet diesel generator is designed to operate efficiently while producing minimal noise. This may involve the use of silent fans, insulated coolant lines, and carefully designed airflow pathways to reduce noise associated with cooling.

associated with cooling.					
Rated Frequency:	50hz 60hz				
Max Output (kw):	2.7 3.0/ 5.0 5.2/ 5.2/5.5/ 6.3 6.9/ 6.8 7.7				
Rated Currency (A):	11.3 12.7/ 20.4 21.8/ 21.8 22.7/ 25.9 27.2/ 27.2 28.6				
Phase No.:	Single Phase				
Insulation Grade:	F				
Excitation Mode:	Self-excitation & Constant Voltage (AVR)				
Receptacle:	Two Receptacles				
DC 12V Output:	Connection Pole Output				
Dry Weight (kg):	164 150 150 153 161				
Noise Level (7m):	72 DB				
Engine Type:	Single Cylinder, Vertical, Four Stroke, Direct Injection, Air-cooled				
Displacement(ml):	296 418 456 498 531				
Compression Ratio:	20:01, 19:01				
Starting System:	Electric Start				
Lube Oil Brand:	CD Grade Or SAE10W-30, 15W-40				
Starting Motor Capacity:	12V 0.9KW/ 12V 1.2KW				
Battery Capacity:	12V 30Ah				
Fuel Tank Capacity (L):	15				
Rated Output(kw):	2.5 2.8/ 4.5 4.8/ 4.8 5.0/ 5.7 6.0/ 6.0 6.3				
Rated Voltage (V):	220V Or As Request				
Rated Rotation Speed (r/min):	3000 3600				
Power Factor:	1				
Pole Number:	2				
Panel Type:	General Panel				
Connection Pole:	Without				
Overall Dmension(mm):	945*555*700				
Working Assorting Weight (kg):	179 185 186 186 187				
Structure Type:	Silent Type				
Cylinder Nobore X Stroke (mm):	1-78x62/ 1-86x72/ 1-88x75/ 1-92x75/ 1-95x75				
Rated Power:	3.68/3000-4/3600. 5.7/3000-6.3/3600. 6.5/3000-7.2/3600. 7.6/3000-8.2/3600. 8.1/3000-8.7/3600				
Lubrication System:	Pressure Splashed				
Fuel Type:	0#(summer)-10#(winter)-35#(chillness) Diesel				
Lube Capacity (L):	1.1/ 1.65				
Charging Generator Capacity:	12V 8.3A				
Fuel Consumption (g/kw*h):	≤280				

Quiet diesel generators are commonly used in settings where noise reduction is crucial, such as residential areas, outdoor events, and locations with noise restrictions. They offer the advantage of providing reliable power while keeping noise disturbances to a minimum. However, it's important to note that even quiet diesel generators will still produce some level of noise during operation, albeit significantly reduced compared to standard generators.



RE MAN	DETHOOF	OFFINANT	GETPOWE	DETMONE	GETONOET	
BE BE Cuturity and Pro 1			9 6			
BE BIS Pales maked (1697)	23 28	65 48	48 83	87.40	40 43	
BA-BIS Man, materal CHAT I	37.30	10 13	8.2 8.8	63.60	48.37	
EEEE Pater volume (5)	DOVERNMENT PRESENT AND ASSESSMENT					
BERGE Paled coverage (4.)	71.9 12.7	204 218	21.8 22.7	20.9 272	272 28.6	
BESIDNE Photocoloxistics speed Colean 1	2001 3600					
ME Floor NO	Bill trigs phase					
SHEET Flower Sector 1 Dog -0 7						
BIR RIS Incustration Concer-						
DE THE HARDE						
BMETIC Excitor mate	BERT (Booth) Set audition & contact votage and to					
ENERG Ford Non	\$355 Seneral Fared					
Bit Bill Pacytoria	WY-WHIRE BIR Ton receptation					
ROSES Consister pais	il Nitrod					
BROC SIV DESIVORAN	MISRIES Committee pole naged					
#R.F-# Grand diseases (L. v'W-xH) Cres.)	947/507/500	845100768	985 555 790	840'000'700	86/55/76	
BE Dy wight I to I	104	160	150	163	182	
SPACE RESIDENCE AND ADDRESS OF THE PARTY OF	179	185	186	100	160	
CONTROL SAN	- 19	79	19	39	79	
BRIDES TRANSPORT	Shed burn					
SIDERS Drave Motor	SETTING OFFINERS OFFINER SETTING OFFINER					
ESPECIAL Drune Type	Way, T.E., 1995, 2019, N.O. Markett Strate Laboratory Contract Contract Proceedings of Contract Contra					
NJEB-IEBNER DYNOU'RD, cook i Broke (mm.)	1-79'90	1-96'72	1-88779	1-975	1-8175	
BME Displacement mr i	296	4.0	450	498	500	
Bilt to Bis No. many Fasted prover	3.56/3000 43800	5,700004,93800	5:5/9008 F.(2/9800)	1.03000 5379000	8.1/9000/4.7/0800	
Elifet Compression ratio	100.04	19101	1891	1994	19101	
RROS Labrication system	E.O. VARRES F. Pressure spinsted					
Bildrift (Searing system	Rich District start					
MIRRIE FLAT NOT	04 (ER) -104 (SR) -564 (SR) SE deal(4 (some) -564 (side) -864 (minus) deal					
BURGAN S Later of Second	CD makes (ME SIA, 160, AC					
REPORT Laboratoria (L.)	1.4	1.66	146	1.86	1.65	
BUT SUFFER Barbon motor capacity (7-445)	120 5,369	127 09/8	SIV EMP	120 1,200	127 1,349	
BASINES Charging generator capacity (V-A)	50V 6.34	100 8.36	SEV AMA	SN 8.34	129 8.56	
DRAME Indeposports (v-An)	100 3046 10V 3046					
BERRE Percenantin Lebert 1	+260	<280	<380	+290	< 380	
MERRE Purton specty (L.)	- 9	19	10	70	15	
BRESTSHIR CORNING GROUP THE 1 N I	- 11	1		- 1		

GET Wuxi Guangertai Power Machinery Co.,Ltd

13813650506



2415819289@qq.com



dieselenginepumps.com

NO.88 Shenxing East Road, Wanshi Town, Yixing City,CHINA