



GET186FA GET192F Diesel Engine Pumps 2.8kw-8.5kw Diesel Water Pump

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: GET
- Certification: ISO CE
- Price: Negotiable
- Delivery Time: 15-20 workdays
- Payment Terms: LC, T/T, PayPal, Western Union, Small-amount payment, Money Gram



Product Specification

- Type: Diesel Water Pump
- Suction/discharger Port Diameter Mm(inch): 50(2'). 80(3'). 100(4'). 150(6')
- Discharge Capacity m³/h): 30 40 110 150
- Total Head Lift: 25m 26m 22m 20m
- Self-priming Time (s/4m): 80 120 180 180
- Max Suction Head: 8m 8m 8m 6m
- Rotation Speed (r/min): 3600
- Noise Level Db(A)/7m): 85
- Overall Dimension(mm): 510x455x640. 560x455x655. 650x470x700. 770x574x785
- Dry Weight: 44kg 50kg 71kg 95kg
- Engine Model: GET173F GET178F GET186FA GET192F
- Rated Power: 2.8kw 4kw 6.3kw 8.5kw
- Fuel Consumption G/kw.h: 288 285 281 281
- Displacement (cm³): 247 300 410 400

for more products please visit us on dieselenginepumps.com

Product Description

Industrial Diesel Engine Pumps Diesel Water Pump Diesel Fire Pump

A diesel fire pump is a specialized type of pump used specifically for fire protection systems. It is designed to provide a reliable and efficient water supply for firefighting applications in buildings, industrial facilities, and other installations.

A diesel water pump is a type of pump specifically designed for transferring or moving large volumes of water in various applications. These pumps are commonly used in construction sites, agriculture, mining, dewatering, irrigation, and other situations where a reliable and efficient water transfer is required.

Model	JBC6/10
Type	vacuum pump
Max.Flow(T/h)	48
MAX.Lift(m)	60
Rated Speed(rpm)	3600
Water Shot Height	35m
Engine	190F
Maximum Suction Height(m)	7
Self-priming Time(S)	20
Discharge Port Diameter(mm)	65
N.W/G.W(KG)	91/100
Dimensions(mm)	
Loading Qty(20GP/40HQ)	
Model	JBC6/15
Type	vacuum pump
Max.Flow(T/h)	54
MAX.Lift(m)	80
Rated Speed(rpm)	3600
Water Shot Height	35
Engine	192
Maximum Suction Height(m)	7
Self-priming Time(S)	20
Discharge Port Diameter(mm)	65
N.W/G.W(KG)	94/103
Dimensions(mm)	
Loading Qty(20GP/40HQ)	



参数表 Specifications

	190F10	190F15	190F20	190F25	190F30
产品型号 Product Model	190F10	190F15	190F20	190F25	190F30
额定流量 Rated Flow (T/h)	48	54	60	66	72
最大扬程 Max. Lift (m)	60	80	100	120	140
额定转速 Rated Speed (rpm)	3600	3600	3600	3600	3600
发动机排量 Engine Displacement (L)	1.9	1.9	1.9	1.9	1.9
额定功率 Rated Power (kW)	13.5	15.0	16.5	18.0	19.5
净重 Net Weight (kg)	91	94	100	105	110
总重 Gross Weight (kg)	100	103	109	114	119
外形尺寸 Overall Dimensions (mm)	440x340x340	440x340x340	440x340x340	440x340x340	440x340x340
包装尺寸 Packing Size (mm)	440x340x340	440x340x340	440x340x340	440x340x340	440x340x340
发动机型号 Engine Model	190F10	190F15	190F20	190F25	190F30
额定功率 Rated Power (kW)	13.5	15.0	16.5	18.0	19.5
额定转速 Rated Speed (rpm)	3600	3600	3600	3600	3600
额定流量 Rated Flow (T/h)	48	54	60	66	72
最大扬程 Max. Lift (m)	60	80	100	120	140
净重 Net Weight (kg)	91	94	100	105	110
总重 Gross Weight (kg)	100	103	109	114	119
外形尺寸 Overall Dimensions (mm)	440x340x340	440x340x340	440x340x340	440x340x340	440x340x340
包装尺寸 Packing Size (mm)	440x340x340	440x340x340	440x340x340	440x340x340	440x340x340

GET Wuxi Guangertai Power Machinery Co.,Ltd



13813650506



2415819289@qq.com



dieselenginepumps.com

NO.88 Shenxing East Road, Wanshi Town, Yixing City, CHINA