



GET Diesel Engine Pumps 4 Inch 6 Inch Diesel Water Pump

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: GET
- Certification: ISO CE
- Price: Negotiable
- Delivery Time: 15-20 workdays
- Payment Terms: LC, T/T, PayPal, Western Union, Small-amount payment, Money Gram



Product Specification

- Type: Diesel Water Pump
- Suction/discharger Port Diameter Mm(inch): 50(2'). 80(3'). 100(4'). 150(6')
- Discharge Capacity m³/h): 30 40 110 150
- Total Head Lift: 25m 26m 22m 20m
- Self-priming Time (s/4m): 80 120 180 180
- Max Suction Head: 8m 8m 8m 6m
- Rotation Speed (r/min): 3600
- Noise Level Db(A)/7m): 85
- Overall Dimension(mm): 510x455x640. 560x455x655. 650x470x700. 770x574x785
- Dry Weight: 44kg 50kg 71kg 95kg
- Engine Model: GET173F GET178F GET186FA GET192F
- Rated Power: 2.8kw 4kw 6.3kw 8.5kw
- Fuel Consumption G/kw.h: 288 285 281 281
- Displacement (cm³): 247 300 410 400

for more products please visit us on dieselenginepumps.com

Product Description

GET Diesel Engine Pumps Diesel Engine Fire Pump

Model	JBC6/10
Type	vacuum pump
Max.Flow(T/h)	48
MAX.Lift(m)	60
Rated Speed(rpm)	3600
Water Shot Height	35m
Engine	190F
Maximum Suction Height(m)	7
Self-priming Time(S)	20
Discharge Port Diameter(mm)	65
N.W/G.W(KG)	91/100
Dimensions(mm)	
Loading Qty(20GP/40HQ)	
Model	JBC6/15
Type	vacuum pump
Max.Flow(T/h)	54
MAX.Lift(m)	80
Rated Speed(rpm)	3600
Water Shot Height	35
Engine	192
Maximum Suction Height(m)	7
Self-priming Time(S)	20
Discharge Port Diameter(mm)	65
N.W/G.W(KG)	94/103
Dimensions(mm)	
Loading Qty(20GP/40HQ)	

Industrial diesel engine pumps are widely used in various applications, including irrigation, construction, mining, oil and gas, and wastewater management. These pumps are designed to provide high-performance pumping capabilities in demanding industrial environments. Here are some key features and characteristics of industrial diesel engine pumps:

Self-Priming Capability: Some industrial diesel engine pumps are equipped with self-priming capabilities. This means they can automatically prime themselves and create suction to draw the fluid into the pump, eliminating the need for manual priming or the use of external priming equipment.

Fuel Efficiency: Industrial diesel engine pumps are designed to be fuel-efficient, optimizing the consumption of diesel fuel during operation. This reduces operating costs, especially in applications where the pump runs for extended periods.

Control and Monitoring Systems: Many modern industrial diesel engine pumps come with advanced control and monitoring systems. These systems allow for remote operation, monitoring of pump performance, and integration with other control systems in the industrial process.

Safety Features: Industrial diesel engine pumps often incorporate safety features to protect the pump system and operators. These may include overload protection, low oil pressure shutdown, temperature monitoring, and emergency stop functions.

Maintenance and Serviceability: Industrial diesel engine pumps are designed for ease of maintenance and serviceability. They typically have accessible components for inspection, routine maintenance, and repairs. Manufacturers may also provide maintenance schedules and guidelines to ensure optimal performance and longevity of the pump.



参数表 Specifications

Model	190F	190F	190F	190F
Model	190F	190F	190F	190F
Max. Flow (T/h)	48	54	60	66
Max. Lift (m)	60	80	100	120
Rated Speed (rpm)	3600	3600	3600	3600
Water Shot Height (m)	35	35	35	35
Engine	190F	190F	190F	190F
Maximum Suction Height (m)	7	7	7	7
Self-priming Time (s)	20	20	20	20
Discharge Port Diameter (mm)	65	65	65	65
N.W/G.W (KG)	91/100	94/103	97/106	100/109
Dimensions (mm)	1100*650*1100	1100*650*1100	1100*650*1100	1100*650*1100
Loading Qty (20GP/40HQ)	10/20	10/20	10/20	10/20