



Lightweight Portable Fire Fighting Pump 2in 3in Diesel Portable Fire Pump

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: GET
- Certification: ISO CE
- Price: Negotiable
- Delivery Time: 15-20 workdays
- Payment Terms: LC, T/T, PayPal, Western Union, Small-amount payment, Money Gram



Product Specification

- Type: Portable Diesel Fire Pump
- Suction/discharger Port Diameter Mm(inch): 50(2"). 80(3"). 100(4"). 150(6")
- Discharge Capacity m³/h): 30 40 110 150
- Total Head Lift: 25m 26m 22m 20m
- Self-priming Time (s/4m): 80 120 180 180
- Max Suction Head: 8m 8m 8m 6m
- Rotation Speed (r/min): 3600
- Noise Level Db(A)/7m): 85
- Overall Dimension(mm): 510x455x640. 560x455x655. 650x470x700. 770x574x785
- Dry Weight: 44kg 50kg 71kg 95kg
- Engine Model: GET173F GET178F GET186FA GET192F
- Rated Power: 2.8kw 4kw 6.3kw 8.5kw
- Fuel Consumption G/kw.h: 288 285 281 281
- Displacement (cm³): 247 300 410 400

for more products please visit us on dieselenginepumps.com

Product Description

Lightweight Portable Diesel Engine Driven Fire Water Pump

The portable fire pump is a lightweight and easy-to-carry fire pump suitable for some special or complex fire emergency scenarios. The following are some application scenarios for portable fire pumps:

1. Fire Fighting Inside Buildings: Portable fire pumps can be used inside buildings, especially in tight spaces or hard-to-reach areas. They provide a high-pressure water source to support firefighters in effective firefighting operations.
2. Wildfire fighting: Wildfires often occur in remote areas or mountainous areas, so traditional firefighting equipment is difficult to reach. Portable fire pumps can be quickly deployed at wildfire scenes through their lightweight design and portability, providing emergency water sources for firefighting efforts.
3. Forest and grassland fire extinguishing: Portable fire pumps can be used to fight forest and grassland fires. Firefighters can carry portable fire pumps into disaster areas and use their high-pressure water flow to extinguish fires to control the spread of fires.

Model	JBC6/10
Type	vacuum pump
Max.Flow(T/h)	48
MAX.Lift(m)	60
Rated Speed(rpm)	3600
Water Shot Height	35m
Engine	190F
Maximum Suction Height(m)	7
Self-priming Time(S)	20
Discharge Port Diameter(mm)	65
N.W/G.W(KG)	91/100
Dimensions(mm)	
Loading Qty(20GP/40HQ)	
Model	JBC6/15
Type	vacuum pump
Max.Flow(T/h)	54
MAX.Lift(m)	80
Rated Speed(rpm)	3600
Water Shot Height	35
Engine	192
Maximum Suction Height(m)	7
Self-priming Time(S)	20
Discharge Port Diameter(mm)	65
N.W/G.W(KG)	94/103
Dimensions(mm)	
Loading Qty(20GP/40HQ)	





13813650506



2415819289@qq.com



dieselenginepumps.com

NO.88 Shenxing East Road, Wanshi Town, Yixing City, CHINA