50mm 80mm Portable Fire Pump Diesel Engine Portable Emergency Fire Pump

Basic Information

- Place of Origin:
- Brand Name:
- Certification:
- Price:
- Delivery Time:

China

GET

ISO CE

- Payment Terms:
- Negotiable 15-20 workdays LC, T/T, PayPal, Western Union, Smallamount payment, Money Gram



Product Specification

• Туре:	Diesel Engine Fire Pump
 Suction/discharger Port Diameter Mm(inch): 	50(2'). 80(3'). 100(4'). 150(6')
• Discharge Capacity m ³ /h):	30 40 110 150
 Total Head Lift: 	25m 26m 22m 20m
• Self-priming Time (s/4m):	80 120 180 180
 Max Suction Head: 	8m 8m 8m 6m
• Rotation Speed (r/min):	3600
 Noise Level Db(A)/7m): 	85
• Overall Dimension(mm):	510x455x640. 560x455x655. 650x470x700 770x574x785
 Dry Weight: 	44kg 50kg 71kg 95kg
Engine Model:	GET173F GET178F GET186FA GET192F
 Rated Power: 	2.8kw 4kw 6.3kw 8.5kw
• Fuel Consumption G/kw.h:	288 285 281 281
	0.47 000 440 400

GET Diesel Engine Fire Pump Diesel Engine For Fire Fighting Pump

The portable fire pump is a lightweight and easy-to-carry fire pump suitable for some special or complex fire emergency scenarios. The following are some application scenarios for portable fire pumps:

1. Rural and remote areas: In rural and remote areas, firefighting resources are limited and firefighting vehicles are difficult to reach. Portable fire pumps can be easily carried to these areas to provide emergency water sources and fire-extinguishing capabilities, helping local residents carry out initial fire fighting.

2. Temporary fire protection systems: Portable fire pumps can be used to set up temporary fire protection systems, especially where there is a lack of fixed water sources or where traditional fire protection equipment is not available. With portable fire pumps, water can be pumped from nearby water sources to establish a temporary water source system to support firefighting efforts.

3. The portability and high-pressure capability of the portable fire pump make it an important fire-fighting equipment, which can provide emergency fire-fighting support in special environments and protect people's lives and property.

Model	JBC6/10		
Туре	vacuum pump		
Max.Flow(T/h)	48		
MAX.Lift(m)	60		
Rated Speed(rpm)	3600		
Water Shot Height	35m		
Engine	190F		
Maximum Suction Height(m)	7		
Self-priming Time(S)	20		
Discharge Port Diameter(mm)	65		
N.W/G.W(KG)	91/100		
Dimensions(mm)			
Loading Qty(20GP/40HQ)			
Model	JBC6/15		
Туре	vacuum pump		
Max.Flow(T/h)	54		
MAX.Lift(m)	80		
Rated Speed(rpm)	3600		
Water Shot Height	35		
Engine	192		
Maximum Suction Height(m)	7		
Self-priming Time(S)	20		
	20		
Discharge Port Diameter(mm)	65		
Discharge Port Diameter(mm) N.W/G.W(KG)			
	65		



G ET Wuxi Guangertai Power Machinery Co.,Ltd						
O	13813650506	2415819289@qq.com	e	dieselenginepumps.com		
NO.88 Shenxing East Road, Wanshi Town, Yixing City, CHINA						