



Dual Fuel Quiet Electric Start Generator White 50hz 60hz Frequency

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: GET
- Certification: ISO CE
- Price: Negotiable
- Delivery Time: 15-20 workdays
- Payment Terms: LC, T/T, PayPal, Western Union, Small-amount payment, Money Gram



Product Specification

- Rated Frequency: 50hz 60hz
- Rated Output(kw): 2.5 2.8/ 4.5 4.8/ 4.8 5.0/ 5.7 6.0/ 6.0 6.3
- Max Output (kw): 2.7 3.0/ 5.0 5.2/ 5.2/5.5/ 6.3 6.9/ 6.8 7.7
- Rated Voltage (V): 220V Or As Request
- Rated Current (A): 11.3 12.7/ 20.4 21.8/ 21.8 22.7/ 25.9 27.2/ 27.2 28.6
- Rated Rotation Speed (r/min): 3000 3600
- Phase No.: Single Phase
- Power Factor: 1
- Insulation Grade: F
- Pole Number: 2
- Excitation Mode: Self-excitation & Constant Voltage (AVR)
- Panel Type: General Panel
- Receptacle: Two Receptacles
- Operation Mode: Without

for more products please visit us on diesenginepumps.com

Product Description

White Dual Fuel Quiet Generator Electric Start Silent Generator

Silent generators are suitable for many different applications due to their noise reduction and portability features. The following are descriptions of several common application scenarios:

1. Indoor Events: The silent generator is ideal for indoor events such as exhibitions, conferences, concerts, etc. Its low noise level won't disrupt events, while its lightweight and portable design makes it easy to move between venues.
2. Camping and Outdoor Activities: A silent generator is an ideal choice during camping and other outdoor activities. They can power camping tents, outdoor barbecues, outdoor lights and more without disturbing other campers or destroying the tranquility of the natural environment.
3. Construction Sites: On construction sites, electricity is needed to power various tools and equipment. Silent generators can provide reliable power supply while reducing noise disturbance to site workers and surrounding residents.
4. Emergency and power outage backup: Silent generators can provide temporary backup power during emergencies or power outages. They can be used for the operation of medical equipment, emergency communication systems, lighting and other basic living facilities to ensure people's safety and convenience.
5. Photography and film shooting: In photography and film shooting, a stable power supply is required to drive photography equipment, lighting and audio equipment, etc. The quiet generator's low noise level and reliability make it ideal for use on film sets.

| | |
|-----------------------------------|--|
| Rated Frequency: | 50hz 60hz |
| Max Output (kw): | 2.7 3.0/ 5.0 5.2/ 5.2/5.5/ 6.3 6.9/ 6.8 7.7 |
| Rated Current (A): | 11.3 12.7/ 20.4 21.8/ 21.8 22.7/ 25.9 27.2/ 27.2 28.6 |
| Phase No.: | Single Phase |
| Insulation Grade: | F |
| Excitation Mode: | Self-excitation & Constant Voltage (AVR) |
| Receptacle: | Two Receptacles |
| DC 12V Output: | Connection Pole Output |
| Dry Weight (kg): | 164 150 150 153 161 |
| Noise Level (7m): | 72 DB |
| Engine Type: | Single Cylinder, Vertical, Four Stroke, Direct Injection, Air-cooled |
| Displacement(ml): | 296 418 456 498 531 |
| Compression Ratio: | 20:01, 19:01 |
| Starting System: | Electric Start |
| Lube Oil Brand: | CD Grade Or SAE10W-30, 15W-40 |
| Starting Motor Capacity: | 12V 0.9KW/ 12V 1.2KW |
| Battery Capacity: | 12V 30Ah |
| Fuel Tank Capacity (L): | 15 |
| Rated Output(kw): | 2.5 2.8/ 4.5 4.8/ 4.8 5.0/ 5.7 6.0/ 6.0 6.3 |
| Rated Voltage (V): | 220V Or As Request |
| Rated Rotation Speed (r/min): | 3000 3600 |
| Power Factor: | 1 |
| Pole Number: | 2 |
| Panel Type: | General Panel |
| Connection Pole: | Without |
| Overall Dimension(mm): | 945*555*700 |
| Working Assorting Weight (kg): | 179 185 186 186 187 |
| Structure Type: | Silent Type |
| Cylinder No. -bore X Stroke (mm): | 1-78x62/ 1-86x72/ 1-88x75/ 1-92x75/ 1-95x75 |
| Rated Power: | 3.68/3000-4/3600. 5.7/3000-6.3/3600. 6.5/3000-7.2/3600. 7.6/3000-8.2/3600. 8.1/3000-8.7/3600 |
| Lubrication System: | Pressure Splashed |
| Fuel Type: | 0#(summer)-10#(winter)-35#(chillness) Diesel |
| Lube Capacity (L): | 1.1/ 1.65 |
| Charging Generator Capacity: | 12V 8.3A |
| Fuel Consumption (g/kw*h): | ≤280 |

